

SUPROTEC

Universal 100

Lubricating composition "SUPROTEC – Universal 100" 100 ml (further LC)



The area of usage

It is intended for treatment internal combustion engines of any type, with a working engine volume from 1.7 l to 2.4 l. (automobiles made in USSR, Russian Federation and other countries before year 2004)

2 or 4 times treatment (internal combustion engine having run less than 50 000 km – 2 treatments, more than 50 000 km – 3 or 4 treatments depending on the level of being worn out)

Application steps:

Step 1:

Refueling is made in working oil (engines having run not less than 5 000 km.) or 1 000 km before next oil replacement.

Before treatment LC "SUPROTEC" it is necessary to mix (shake) the bottle carefully until all of a deposit is dissolved. Then warm up the engine to a working temperature. Next blank off the engine. And pour LC into oil priming mouth. After that start the engine and maintain further in a regular mode for no less than 15-30 minutes.

After 500-1500 km. begin the second stage of treatment

Step 2:

Make oil and oil filter replacement. (in case of serious engine pollution washing is recommended)

Before treatment LC "SUPROTEC" it is necessary to mix (shake) the bottle carefully until all of a deposit is dissolved. Then warm up the engine to a working temperature. Next blank off the engine. And pour LC into oil priming mouth. After that start the engine and maintain further in a regular mode for no less than 15-30 minutes.

Maintain until next regular oil replacement.

Step 3:

Make oil and oil filter replacement.

Before treatment LC "SUPROTEC" it is necessary to mix (shake) the bottle carefully until all of a deposit is dissolved. Then warm up the engine to a working temperature. Next blank off the engine. And pour LC into oil priming mouth. After that start the engine and maintain further in a regular mode for no less than 15-30 minutes.

Maintain until next regular oil replacement.

Make the 4 treatment in case it is required.

The note: LC "Suprotec" is compatible with any type of engine oils. For the engines with working volume from 2.5 l and more the necessity of LC "SUPROTEC Universal 100" is defined from calculation: 50 ml. of lubricant on 1 liter of an engine working volume.